

Omni-Care TENS/EMS



- Dual channel (4-lead) digital combination TENS/Muscle Stim
- 4 TENS / 2 EMS modes
- Treatment timer
- Last setting recall & settings lock
- Compliance monitor
- Parameter lock button
- Power ON/OFF switch
- Battery power indicator
- Attractive high-tech design with metallic finish & LCD display
- Hinged protective cap for intensity dials
- Heavy duty metal belt clip
- Three year warranty
- Comes with 1 pkg of 4 reusable self-adhering electrodes, 1 set 43" pin lead wires, 1 9-volt heavy duty battery, carrying case, and instruction manual



Technical Specifications

Channel Dual, isolated between channels

Amplitude Adjustable 0 - 100 mA, Max output 100 mA peak to peak (21.2 mA rms) into 500 ohm load each channel

Output Voltage Adjustable 0- 50 V, Max output 50 V peak to peak (10.6V rms) into 500 ohm load each channel

Waveform Asymmetrical rectangular biphasic pulse

Pulse Rate Adjustable, 1 ~ 150 Hz, 1Hz / step

Pulse Width Adjustable, 30 ~ 300 μ S; 10 μ S / step

4 TENS Modes Burst, Normal, Pulse Width Modulation, and Pulse Rate Modulation

2 NMES Modes S, A (Simultaneous, Alternating)

NMES Contraction Time Adjustable, 1 ~ 30 sec., 1 Sec./ step

NMES Relaxation Time Adjustable, 1 ~ 60 sec., 1 Sec./ step

NMES Ramp Time Adjustable, 1 ~ 6 sec., 1 Sec./ step

Timer Adjustable, 1 ~ 60 minutes, 1 min/ step, and continuous

Power Supply One 9-volt battery, type 6F22

Size 9.5 x 6 x 3 cm

Weight 120 grams including battery



Distributed by:



217 Industrial Court
Wabasha, MN 55981

1-800-363-STIM | www.medi-stim.com

Fax: 1-651-565-2410